Tgo



video control beyond the box





Video Control at your Fingertips

Portable and lightweight, Tgo goes wherever control is needed. The compact format contains not just a 8 inch touch screen display, but also the power of XPOSE® controls. Connect remote preview enabled processors directly to one of the gigabit LAN ports to not only switch between presets but also preview source video directly on Tgo. Enhance video control operations by adding an extended monitor and peripherals including keyboard and mouse to create the ultimate video control station.

Features

- · Standalone XPOSE powered video control
- · 8 inch touch screen
- · Preview source video and presets
- · Customisable touch keys
- · Multiple direct Gigabit ethernet connections
- · USB3.0 support for external peripherals
- · HDMI port for monitor







Designed for You

Tgo is equally at home for events and installation applications with options for not only desktop use, but also wall mounting and rack mounting

Preset Control

Recall presets from connected processors, previewing directly on the Tgo display before switching to output.

Multi-mode support is available for processors configured with differing operations. Select presets from across multiple banks on the selected processor.

PST	PGM	SAVE	LOAD	PVW
1	2	3	4	Ą
5	6	7	8	O
9	10	11	12	СИТ
13	14	15	16	TAKE

Custom Layouts

Customise buttons with icons and/or text, tailoring Tgo to specific applications or events.



Extend

Add USB keyboard and mouse for more control and connect an external HDMI monitor to take full control of configuration and control possibilities on demand.




Multi-View

Display video sources in configurable multi-views.




Live Presets

View presets with live video previews on the Tgo display when connected to enabled processors.




Centralised Control

Control complete systems of not just multiple displays, but also multiple devices from across the X universal processor and FLEX/FLEXpro range.










Specification

	Input	H.264	4×RJ45	
			1.15.15	
	Output	HDMI 2.0	1×HDMI-A	
	Audio	Audio	1×3.5mm Stereo Jack	
	Communication	LAN	4×RJ45	
		USB 3.0	2×USB-A	
		USB 2.0	1×USB-A	
	Power		1×DC Jack	
	Input Resolutions	H.264		
	mpat resolutions		176×144 240×180 320×180 320×240 320×256 352×228 352×480 400×224 400×320 480×270 480×272 480×320 480×360 480×480 544×480 608×448 640×360 640×480 704×576 720×404 720×480 720×540 720×576 850×480 1024×576 1280×720 1680×1056 1920×1080	
Performance	Output Resolutions	HDMI		
remainee	(Monitor)	SMPTE	720p@23.98/24/25/29.97/30/50/59.94/60 1080i@23.98/24/25/29.97/30/50/59.94/60 1080p@23.98/24/25/29.97/30/50/59.94/60 2160p@24/30/50/60	
		VESA	800×600@60 1024×768@60 1280×768@60 1280×1024@60 1366×768@60 1600×1200@60 1920×1080@60 2048×1152@60 2560×1600@60 3840×2160@30	
		H.264	MPEG-4/AVC	
	Supported Standards	HDMI	2.0	
	(Monitor)	USB	3.0	
Power	Input Voltage	DC 12V/1.5A		
Environment	Temperature	0°C ~ 45°C		
	Hudmidity	10%~85%		
Physical	Weight	Net (Device)	1.5kg	
		Packaged	3kg	
	Dimension	Net (Device)	200mm×162mm×40.5mm	
		Packaged	308mm×269mm×150mm	

Order Codes

Product Code	Item
250-1000-01-0	Tgo
900-2005-01-0	Fitted Flight Case
980-1000-01-0	Rack Accesories-Tgo

Dimensions



200mm



